



En137 6.8L Positive Pressure Breathing Apparatus Self Contained 9 Kgs Scba

Our Product Introduction

for more products please visit us on multi-gasdetection.com

Basic Information

- Minimum Order Quantity: 1PC
- Stock: 1PC




Product Specification

- Model NO.: KL99
- Warranty: 1 Year
- Certificate: Ce: En137
- Transport Package: Orange Plastic Carton
- Specification: 75x47.5x31cm
- Trademark: KELISAIKE
- Origin: Jiangsu, China
- HS Code: 9020000000
- Supply Ability: 1000sets Per Month
- Volume Of Cylinder: 2L, 3L, 4.7L, 6.8L, 9L
- Cylinder Material: Carbon Fiber Composites
- Working Pressure: 30MPa
- Gas: Compressed Air
- Service Time: 6.8L For 60 Mins
- Weight: 9 Kgs



More Images



Product Description

Positive Pressure Self Contained Air Breathing Apparatus SCBA

» Product Detail

KL99-SCBA



CE/ MED approved, meeting
EN137, EN136 standards.

Air Cylinders: More robust and safer four-layer composite structure design; aluminum alloy inner bladder; carbon fiber; glass fiber; epoxy resin



Reduced Pressure Assembly:
Stable output pressure of the compressor. Despite featuring a small volume carbon fiber tank, the high pressure air in the tank can be quickly converted to standard low pressure breathable air.

Full Mask: Plug- in structure for quick connection with the demand valve; Leak tight mask, made of high quality flame resistant silicon rubber; Top silicon rubber oronasal cover, soft and high temperature resistant; Flame resistant reticulated hood and strap, easy to wear; High-intensity sound transmission diaphragm.



- **Back Plate Assembly** Consisting of a back plate, shoulder straps, a waist belt, a buckle, a pressure reducer holder and a cylinder fastener. Designed according to ergonomics, complying with the back shape of 5. human body.
- **Injection moulded**, with flame resistant engineering plastics and carbon fiber. The shoulder straps and belt are made of Nomex or KEVLAR, tear- resistant and flame-retardant.

This positive pressure air breathing apparatuses are self-contained open breathing apparatuses. This series of products, which are ideal personal breathing protectors for the fireman and emergency rescuer, are widely used in such sectors as fire fighting, chemical industry, shipping, petroleum, smelting, electricity, warehouse, lab, mine, for the firemen and emergency rescuers to perform effectually rescue and relief work under the conditions of heavy smoke, poison gas, steam and hypoxia, etc.

>>> Specification

Volume of the gas cylinder	6.8L	
Cylinder material	Carbon fiber composites	
Service time	≥60mins at 30L/min	
Working pressure	30MPa	
Hydrostatic pressure	45MPa	
Overall weight	9kg(air not included)	
Gas	Compressed air	
Standard	CE: EN137	
Type	KL99-6.8L/30	KL99-9L/30
Working pressure(MPa)	30	30
Volume of the gas cylinder(L)	6.8	9
Max flow(L/min)	300	300
Inhalation resistance(Pa)	<588	<588
Exhalation resistance(Pa)	<687	<687
Alarm pressure(MPa)	4-6	4-6
Serive time(min)	60	90
Overall weight(kg)	9	≤11
Alarm voice	≥90dB	≥90dB

A set fire works firing equipment contain with parts as following:



1. KL99-A01 full mask

The full mask is adaptable to fit all different shapes of faces. It is made of flame-retarded silicone, safe and comfortable to wear. It is also antifog designed. It allows for a wide field of vision. And the visor is made of a high impact scratch resistant material, which prolongs its life by 3-4 times.

2. KL99-A02 backboard

It is designed according to ergonomics to fit different users. The main body's weight is only 0.685kg. The tortuosity can be above 90 degree. It is made from a high strength material, which is chemical, high temperature and impact resistant.

3. KL99-A03 warning whistle and pressure gauge

The warning whistle is integrated with pressure gauge and located on the chest after donning. It will give a continuous 90dB alarm to make sure the user can hear it under noisy environment.

The pressure gauge is waterproof and shockproof designed, and it can be read in the darkness.

4. KL99-A04 backpack

Flexible backpack, equipped with comfortable and detachable tourne, makes waist and shoulders no oppressive feeling. Shoulder straps and belt are made of Nomex or KEVLAR, tear-resistant and flame-retardant. And they together distribute the weight of the apparatus effectively.

5. KL99-A05 air supply valve

Handhold valve, with small size, can be inserted mask in 360o promptly. Gas supply is above 500L/min.

6. KL99-A06 decompressor

The decompressor core adopts advanced technology with a design life of 15 years. The unique maximum gas supply is above 1000L/min, which make sure the user's enough respiratory volume.

7. Gas cylinder and cylinder valve

Carbon fibre cylinder has the advantages of high strength, light weight, corrosion-resistant and anti-shocking.

Y-shape self-locking cylinder valve effectively avoid opening the valve caused by accidental collision or misoperation.

8. Multifunctional fast join valve

Stainless steel, strong and durable. Traceless design, safe and reliable.

9. The configuration can be 2L/3L/4.7L/6.8L/9L

Carbon fibre cylinder, internal is made of corrosion-resistant aluminum alloy, and the middle layer is carbon fibre. The glass fiber surface screw is M18*1.5.

>>>Standard packing

1 set in one carton, inside packing: yellow plastic suitcase, outside packing: carton box.

>>> CE Certificate:

» Our Certificates



We have obtained **CE, ISO** and other international certificates
for different market requirements.



Nanjing Kelisaike Safety Equipment Co., Ltd.



+86 25 8719 3262



manager@njklsk.cn



multi-gasdetection.com

Bldg 12, 2 Qingshuiting West Road, Nanjing, Jiangsu, China, 211102