



## Customized 300 Bar Scba Air Compressor High Efficiency For Firefighting Use

### Our Product Introduction

#### Basic Information

- Certification: CE, ISO, GL/EC
- Minimum Order Quantity: 1PC
- Stock: 1PC




#### Product Specification

- Model NO.: KL99
- Type: Air Breathing Apparatus
- Material: PE
- Transport Package: Carton
- Trademark: KELISAIKE
- Origin: Nanjing, China
- HS Code: 90200000
- Supply Ability: 1000PCS
- Package Size: 49.00cm \* 31.00cm \* 47.00cm
- Package Gross Weight: 20.000kg
- Application: Firefighting And Diving
- Using Field: Air
- Suitable For: Adult
- Customization: Available | Customized Request
- Shipping Cost: About Shipping Cost And Estimated Delivery



#### More Images



**Product Description****CE certified Mobile High Pressure Compressor for Compressing Air and Breathing Air****Mobile High Pressure Compressor for Compressing Air and Breathing Air**

移动式空气/呼吸空气压缩机

Types:

**JUNIORII-B | JUNIORII-E | JUNIORII-W**

Production status: F01



JUNIOR II-E



JUNIOR II-W



JUNIOR II-B

<b>General</b>	
Medium 介质	Air 空气
Intake pressure 进气压力	Atmospheric 常压
Operating pressure 运行压力	225 bar / 330 bar, depending on setting of final safety valve 根据使用的安全阀
Allowed ambient temperature 使用环境温度	+5...+45 °C
Allowed altitude 海拔允许范围	0...1500 MSL 0-5000 米
Sound pressure level 声压	83 dB (A) 83 分贝
Sound power level 声功率	95 dB (A) 95 分贝
Control voltage (optional) 控制箱电压 (选配)	24 V AC, 50/60 Hz 24 V 交流电 50/60Hz
Compressor oil standard 压缩机润滑油	synthetic 合成油
Compressor oil intervals 换油周期	synthetic: 1x per year / 2000 hrs 合成油 每年或每 2000 小时 先到为准

<b>Compressor unit</b>	
Charging rate 流量	100 l/min (6 m <sup>3</sup> /h)
Filling pressure 充气压力	PN 200 / PN 300
Setting, final safety valve 安全阀设定	max. 225 bar / 330 bar 最大 225 bar / 330 bar
Setting, final pressure sensor (optional) 末级压力传感器设定 (选配)	max. 220 bar / 320 bar 最大 220 bar / 320 bar
Purification system 过滤系统	P 21
Power electric motor 电机功率	2,2 kW
Required cooling air flow, min. 冷却空气流量要求	660 m <sup>3</sup> /h
Max. Inclination 最大倾角	5°
Weight in kg (standard version) 重量 (标准设备)	approx. 46 kg

1- phase motor 单项电机	
Power 功率	2.2 kW
Voltage <sup>1</sup> 电压	230 V
Frequency 频率	50 Hz
Rated current 电流	13.2 A (bei 230 V/50 Hz)
Speed 转速	2850 rpm
Protection class 防护等级	IP55 (TEFC)
Rotation 转向	Left 向左
Weight 重量	24 kg

1 Different voltage / frequency at additional charge.  
不同电压/频率 额外收费

#### Standard scope of supply compressor unit:

##### 压缩机的标准供货范围

- Compressor block
- 压缩机主机
- Drive
- 驱动
- Purification system
- 过滤系统
- Filling devices
- 充气装置
  
- Motor protection switch
- 马达保护开关
- B-TIMER
- B-TIMER 电子计时器

#### Standard scope of supply:

##### 分项供货范围

###### ➤ COMPRESSOR BLOCK

###### 压缩机主机

- Splash lubrication
- 飞溅润滑
- Micronic intake filter: 10 µm
- 微尘进气过滤器: 10 µm
- Intermediate coolers, air cooled
- 中间级冷却器, 风冷
- Aftercooler, air cooled, outlet temperature max. 10-15 °C above cooling air temperature
- 末级冷却器, 风冷, 出口温度比环境温度高 10-15 度
- Intermediate separators after the 2<sup>nd</sup> stage
- 中间级油水分离器, 二级后
- Final separator for removal of oil-/water condensate
- 末级油水分离器
- Safety valves after each stage, TÜV approved final pressure safety valve (option)
- 各级后安全阀, 末级安全阀 TÜV 认证 (可选)
- Pressure maintaining and check valve after the final stage
- 末级后保压阀及止回阀

Dimensions (LxWxH) standard version 尺寸 (长 x 宽 x 高) 标准设备	655 x 360 x 415 mm
Dimensions (LxWxH) with automatic condensate drain and final pressure switch off 尺寸 (长 x 宽 x 高) 带冷凝水自动排放和末级压力停机的设备 (选配)	760 x 430 x 480 mm

## » Our Certificates



We have obtained **CE, ISO** and other international certificates for different market requirements.



## THE WORKSHOP

Nanjing KELISAIKE has passed IS9001 International Quality System Certification, which ensures all products' excellent performance and competitive prices.



## THE EXHIBITION

We often participate in exhibitions at home and abroad, harvest a lot of friends, and have been confirmed by many partners.



Nanjing Kelisaike Safety Equipment Co., Ltd.



+86 25 8719 3262



manager@njklsk.cn



multi-gasdetection.com

Bldg 12, 2 Qingshuiting West Road, Nanjing, Jiangsu, China, 211102