



## High Precision PM2.5 PM10 Industrial Air Quality Monitor with Temperature Control

### Our Product Introduction

#### Basic Information

- Place of Origin: Jiangsu, China
- Brand Name: KELISAIKE
- Certification: CE
- Model Number: AQMS-H6
- Minimum Order Quantity: 1PC
- Price: \$3,000.00-6000 PC
- Packaging Details: AQMS in Wooden case
- Stock: 1PC



#### Product Specification

- Warranty: 1 Year
- Type: Gas Analyzer, AQMS-H6
- Customized Support: OEM, ODM
- Name: AQMS Air Quality Monitoring System
- PM2.5: (0~10000)  $\mu\text{g}/\text{m}^3$
- PM10: (0~10000)  $\mu\text{g}/\text{m}^3$
- Indication Error:  $\pm 15\%$
- Resolution: 0.1  $\mu\text{g}/\text{m}^3$
- LOD: 2  $\mu\text{g}/\text{m}^3$
- Sampling Flow: 2.83 L/min, precision  $\pm 2.5\%$ , With The Cyclone Cutter
- Grain Size: PM2.5, PM10 Or TSP
- Temperature Control: (10~60)
- Highlight: PM2.5 Industrial Air Quality Monitor, PM10 Industrial Air Quality Monitor, PM2.5 Ambient Air Quality Monitoring System



#### More Images



## Product Description

### High precision AQI air quality monitoring station dust particulate matters PM2.5 PM10 monitoring system

#### Product Description

##### Introduction:

**Micro Ambient Air Quality Monitoring System** is an economical product for providing real-time and accurate detection of outdoor air pollutants, with the performance close to the level of automatic monitoring system. Compared with lower price alternatives on the market, H6 provides accurate detection data comparable to standard stations. After calibration on site according to certified reference standards, it can reach the optimal traceability. Therefore, as an air quality monitoring system, it has high cost efficiency.

##### Main Features:

- No need to change the sample cutter, able to measure the mass concentration of PM10 and PM2.5
- On-site calibration according to traceable reference standards;
- Optional zero gas calibration modules;
- Imported high precision four-electrode sensors;
- Modular design for configuration of any combination, easy to set different monitoring parameters on demand, suitable for large-scale grid distribution points
- Embedded processor of industrial grade for the circuit, suitable for harsh outdoor environments, with working environment temperature range of -50 to 100 °C;
- Dynamic heating control for air particulate sampling to remove the influence of water and fog on the measured data;
- An electronic flowmeter used to measure the sampling flow speed of particulates and gaseous pollutants.
- Stable and reliable data transmission with the industrial grade data transmission module;
- Dual-channel communication mode to realize communication in extreme cases and ensure data continuity;
- Modular design, and high reliability CAN bus communication between modules; automotive electronic communication protocol to ensure the stability of the system;
- Remote data transmission and system state information readable remotely, as well as remote control, remote modification of instrument parameters, and fault diagnosis;
- Remote upgrade of terminal applications via the FTP server to realize tele-maintenance and ensure that users can use the latest applications and update system functions timely;
- Optional five meteorological parameters tester;
- Optional IP cameras with various parameters to ensure night and visual range shooting requirements, with automatic snapshot and real-time monitoring functions.
- On-site real-time data display: end instruments renew data every 5 seconds.
- The optional data service platform can display average minute, hourly and daily values. Report analysis function can generate daily, monthly and yearly reports, as well as trend reports. Same screen multi-points display, supporting mobile terminal data query and data push to the display terminal;
- Various installation methods, to be selected according to the site situation: support, pole, etc. Each type of mounting is tight and secure and can resist the instantaneous 12 level wind force.

##### Technical Parameters:

Gases	Measurement range(ppb)	Resolution (ppb)	LOD(ppb)	24 h drift zero / ppb
O3	0-1000	1	≤10	5%F.S
NO2	0-1000	1	≤10	5%F.S
CO	0-20000	1	≤150	5%F.S
SO2	0-1000	1	≤10	5%F.S
H2S(optional)	0-20000	1	≤150	5%F.S
VOC(optional)	0-40000	1	≤150	5%F.S

##### Particulates:

Measurement range	PM2.5:(0~10000) $\mu\text{g}/\text{m}^3$ , PM10:(0~10000) $\mu\text{g}/\text{m}^3$
Indication error	±15%

Sampling flow	2.83 L/min,precision $\pm 2.5\%$ , with the cyclone cutter
Grain size	PM2.5, PM10 or TSP
LOD	2 $\mu\text{g}/\text{m}^3$
Resolution	0.1 $\mu\text{g}/\text{m}^3$
Temperature control	(10~60) ,temperature control accuracy $\pm 1$
Data storage	Up to one year
USB interface	Support USB data export
Remote data query	DTU module for remote query of instrument working status and real-time measurement data
Fault Alarm	Real-time display of fault alarm
Air intake heating	Dynamic heating of intake tube and Automatic temperature and humidity compensation

**Optional  
Meteorological parameters:**

Temperature	Measuring range:-50 ~100	RH	Measuring range: 0~100%RH	
	Resolution: 0.1		Resolution: 0.1%RH	
	Accuracy: $\pm 0.5$		Accuracy: $\pm 3\%$ RH	
Wind speed	Measuring range: 0~70m/s		Resolution: 0.1m/s	
	Start wind speed $\geq 0.5\text{m/s}$		Accuracy: $\pm 0.3\text{m/s}$	
Wind direction	Measuring range: 0~360°		Resolution: $\pm 0.1^\circ$	
	Start wind speed $\geq 0.5\text{m/s}$		Accuracy: $\pm 3^\circ$	
Atmospheric pressure	Measuring range: 10~1100hpa			
	Resolution: 0.1hpa			
	Accuracy: $\pm 0.5\text{hpa}$			

**Noise Parameters**

Noise	IEC61672:2002 level 2 GB/T3785-2012 level 2 Level 1 noise level meter available	Frequency range	16~20KHz
Measurement range	30~140 dB	Frequency weighting	A, C, Z
Principle of noise sensor: High precision capacitive free-field microphone			

**Main Qualifications**

CCEP China Certification of Environmental Products  
CMA Test Report

**Company Information**

## » About Us



## COMPANY APPEARANCE

### THE OFFICE MEETING



### WORKSHOP INSTRUMENT



- Nanjing Kelisaike Safety Equipment Co., Ltd. founded in **2004**, Nanjing Kelisaike has three subsidiaries in Beijing, Xi'an and Xinjiang province, and over **30** domestic sales service centers.
- Standard products include the K60 series portable single gas detectors, K60-IV series multi gas detectors, K800 series fixed gas transmitters, K500 series wall-mounted gas detectors, K1000 series gas detector control panel units, KL99 series air breathing apparatuses, etc.
- Nanjing Kelisaike is also a factory with rich experience in **OEM** service, providing professional design and manufacturing of customized products.

## » Our Certificates



We have obtained **CE**, **ISO** and other international certificates for different market requirements.

» Our Exhibition



Nanjing Kelisaike Safety Equipment Co., Ltd.



+86 25 8719 3262



manager@njklsk.cn



multi-gasdetection.com

Bldg 12, 2 Qingshuiting West Road, Nanjing, Jiangsu, China, 211102