



Portable Handheld Natural Gas Detector H2S BW Honeywell With Simple Operation

Our Product Introduction

Basic Information

- Place of Origin: Jiangsu, China
- Brand Name: BW, BW Honeywell
- Minimum Order Quantity: 1PC
- Price: \$699.00/sets >=1 sets
- Packaging Details:
 1. PAPR Portable Powered Air Purifying RespiratorY
 2. One safety carton box
 3. One box in carton, carton size: 60*45*20cm
- Stock: 1PC
- Supply Ability: 1000 Set/Sets per Year



Product Specification

- Warranty: 1 YEAR
- Type: Gas Detector, Multi Gas Detector, Multi Gas Detector
- Customized Support: OEM
- Humidity Range: 10%-100%
- Sensor Range: H2S (0-200ppm), CO (0-1000ppm), O2 (0-30%vol), LEL (0-100%LEL)
- Temperature Range: -20 ~50
- Alarm Type: Audible, Visual, Vibrating
- Battery Run Time: 8-13hours
- Standards: Class I, Division 1, Groups A, B, C, D
- Datalogging: 375 Hours At 15-second Intervals
- Benefits: Integrated Sampling
- Port: FOB Nanjing / FOB Shanghai
- Highlight: Portable Handheld Natural Gas Detector, Simple Operation Handheld Natural Gas



More Images



Product Description

BW Gas Detector

Product Description

Go the distance and save with this smart, simple and economical way to compliance. Product Overview: Honeywell BW™ Max XT II is the smart, simple, and economical way to compliance. Workers feel safe and incidents are minimized so everyone will be able to do more. That means savings realized from business continuity and productivity. Simple operation, with SmartSample pump. Honeywell BW™ Max XT II reliably monitors up to four hazards and combines straightforward one-button operation with our robust, motorized pump for intelligent, remote sampling, ideal for confined spaces. The Honeywell BW™ Max XT II is fully compatible with MicroDock II automated test and calibration system.

Features & Benefits:

Monitors H2S, CO, O2 and combustibles

One-button operation with robust, motorized pump

Compatible with MicroDock II

Quick Specs:

Size: 5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm

Weight: 11.5 oz. / 328 g

Temperature: -4 to 122°F / -20 to 50°C

Readily enables to communicate with Motorola MOTOTRBO

GasAlert **MaxXT II**



Simple operation with pump

The rugged GasAlertMax XT II reliably monitors for up to four gas hazards and combines straightforward one-button field operation with an integrated sampling pump. Tamper-proof, user-adjustable options enable the instrument to be customised to suit your application. Confined space entry and remote sampling have never been so easy with new, intelligent SmartSample pump technology. Minimise pump blockages and improve remote sampling result accuracy. Powered by a rechargeable battery pack that provides runtime for an entire 13 hour shift, the compact GasAlertMax XT II comes with standard event logging and datalogging. The GasAlertMax XT II is fully compatible with the MicroDock II automated test and calibration system.

H₂S**CO****O₂****LEL**

Standard Package Contents

- Detector complete with specified sensor(s), stainless steel alligator clip and concussion-proof housing
- Rechargeable lithium polymer battery
- Charging adaptor
- 3 ft. / 1 m calibration hose with quick connect
- 10 ft. / 3 m sampling hose with particulate filter and quick connect
- Reversible screwdriver
- Kit of five spare pump filters
- Manual
- Multi-language CD manual

General Specifications

Size	5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 6.2 cm
Weight	11.1 oz. / 316 g
Typical battery life	13 hours @ 32°F / 0°C 10 hours @ 4°F / -20°C Recharges in 6 hours
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D  American Bureau of Shipping  Xg II 1 G  Ga Ex ia IIC T4  Ga Ex ia IIC T4  European Conformity
Warranty	Full two year warranty including all sensors

GasAlertMax XT II

4 - G A S D E T E C T O R W I T H P U M P

Order Number			
	Yellow	Black	
GasAlertMax XT II 4-Gas Detector			
%LEL, O ₂ , H ₂ S, CO	XT-XWHM-Y-NA	XT-XWHM-B-NA	
GasAlertMax XT II 3-Gas Detector	Yellow	Black	
%LEL, O ₂ , H ₂ S	XT-XWHO-Y-NA	XT-XWHO-B-NA	
%LEL, O ₂ , CO	XT-XW0M-Y-NA	XT-XW0M-B-NA	
O ₂ , H ₂ S, CO	XT-XOHM-Y-NA	XT-XOHM-B-NA	
%LEL, H ₂ S, CO	XT-0WHM-Y-NA	XT-0WHM-B-NA	
GasAlertMax XT II 2-Gas Detector	Yellow	Black	
%LEL, O ₂	XT-XW00-Y-NA	XT-XW00-B-NA	
H ₂ S, CO	XT-0OHM-Y-NA	XT-0OHM-B-NA	
O ₂ , H ₂ S	XT-XOHO-Y-NA	XT-XOHO-B-NA	
O ₂ , CO	XT-X00M-Y-NA	XT-X00M-B-NA	
%LEL, H ₂ S	XT-0WHO-Y-NA	XT-0WHO-B-NA	
%LEL, CO	XT-0W0M-Y-NA	XT-0W0M-B-NA	
GasAlertMax XT II 1-Gas Detector	Yellow	Black	
O ₂	XT-X000-Y-NA	XT-X000-B-NA	
%LEL	XT-0W00-Y-NA	XT-0W00-B-NA	
H ₂ S	XT-0OHO-Y-NA	XT-0OHO-B-NA	
CO	XT-000M-Y-NA	XT-000M-B-NA	
GasAlertMax XT II Region Codes			
For orders outside the North America, change order number suffix "-NA" to:			
"-EU"	Europe	"-BR"	Brazil
"-NA"	North America	"-OR"	Other region with 3-pin UK plug
"-AU"	Australia	"-OE"	Other region with 2-pin UK plug
"-CN"	China/New Zealand		
Gas Legend			
%LEL	Combustible		
O ₂	Oxygen		
H ₂ S	Hydrogen sulphide		
CO	Carbon monoxide		

product catalog



K60B

K60

K60-IV

K60-IV-P

Fixed/Wall-Mounted Gas Detector (Controller)



K800



K500



K700



K1000

Online Gas Analyzer and CEMs



KF200



KF100



WT602



CEMs



AQMS

Breathing Safety Apparatus



EEBD



SABA



SCBA



FBCAR



PAPR

Other product



Radon

BW gas detector

Gas sensor



Nanjing Kelisaike Safety Equipment Co., Ltd.



+86 25 8719 3262



manager@njklsk.cn



multi-gasdetection.com

Bldg 12, 2 Qingshuiting West Road, Nanjing, Jiangsu, China, 211102