

Customizable Fixed Gas Monitor NH3 Wall Mounted Type For Industrial Use

Our Product Introduction

for more products please visit us on multi-gasdetection.com

Basic Information

- Minimum Order Quantity: 1PC
- Price: \$195/sets >=1 sets
- Stock: 1PC



Product Specification

- Warranty: 1 year
- Customized Support: OEM
- OEM: YES
- Material: Stainless Steel/Aluminium Magnesium Alloy
- Usage: Guarantee The Safety Of Industrial Production
- Working Voltage: 24V DC
- Sensor Life: 2 Years
- Gas Detected: Carbon Monoxide
- Aspiration: Diffusion
- Explosion-proof Grade: Exd II CT6
- Working Temperature: -20°C~+50°C
- Type: Non-display, Display, Display With Acousto-optic
- Highlight: Customizable Fixed Gas Monitor, Wall Mounted Fixed Gas Monitor,



More Images



Product Description

UL SIL3 Approved Wall Mounted NH3 Industrial Use Gas Detector



Product Description

K800 Series Fixed Gas Transmitter provides comprehensive monitoring of combustible, toxic gas hazards in potentially explosive atmospheres, indoors and outdoors—and is marked by installation ease and flexibility, user-friendly operation and cost-effective gas monitoring.

>>>Key Features

- 1) Providing digital LCD displayer, alarm facility with sound and light, and solid relay output on the spot, allowing contol the equipments easily.
- 2) Supporting 4 to 20mA analog signal output (DC24V), connecting with the remote host contoller, and having direct access to the DCS.
- 3) Connecting 3 - core shield cable, 3x1.0mm.
- 4) Special transmitter mounting kit making the installation and performing calibration easier and better
- 5) Ambient temperature: -20°C~+50°C
- 6) Explosion-proof grade: ExdIICT6
- 7) High sensitivity, short response time and good stabilization

K800 Fixed Gas Detector





UK sensors (brands CITY, Alphasense, Dynament etc.), US (brand Honeywell), Japanese and German sensors, ensuring high stability & sensitivity

CE/ATEX approved. Gas detectors are approved under the ATEX directive.



Larger & stronger LED screen: easy for reading; able to work in environments with -4°F to 122°F (-20°C – $+50^{\circ}\text{C}$), 0 – 95% RH, non-condensing (anti-splash)

- **High response speed:** Specially designed main board for industrial use; 10+ years professional engineering team for technical solutions
- **OBM/ ODM/ OEM Service:** with over 14 years experience, specializing in gas detectors.



Product Parameters

Item	Fixed Gas Detector
Sensor Cell	UK sensors (brand CITY, Alphasense, Dynament etc.), US (brand Honeywell), Japan and Germany sensors
Lifetime of detector	2 – 5 years
Sample mode	Diffusion
Output signals	4-20mA/RS485
Operating voltage	24V DC
Display	LCD display
Transmission cable	Three core shield cable

Ambient temperature	- 40 ° C ~ + 50 ° C
Relative humidity	15~95%RH(non condensation)
Working Pressure	86~106Kpa
Detection precision	±5%FS
Net Weight	<1kg
Explosion-proof grade	Exd II CT6

Gas Types	Detection range	Response Time	Resolution	Alarm Values
CO	0-25%vol/30%vol	T90≤20s	0.1%vol	18.0%vol/23.0%vol
H ₂ S	0-100%LEL	T90≤30s	1%LEL	25.0%LEL/50.0%LEL
SO ₂	0-1000 ppm/2000ppm	T90≤30s	1 ppm	50ppm/100ppm
Cl ₂	0-200 ppm	T90≤30s	0.1 ppm	10ppm/20ppm
NH ₃	0-200ppm	T90≤30s	0.1 ppm	2 ppm /10 ppm
NO ₂	0-20 ppm	T90≤30s	0.1 ppm	1 ppm /10 ppm
NO	0-100ppm/2000ppm	T90≤50s	1 ppm	25 ppm /50 ppm
O ₃	0-200ppm	T90≤25s	0.1 ppm	3 ppm /10 ppm
PH ₃	0-1000 ppm	T90≤50s	1 ppm	25 ppm /50 ppm
H ₂	0-5ppm/20ppm	T90≤30s	0.1ppm	0.3ppm/5ppm
HF	0-10ppm	T90≤60s	0.1ppm	0.3ppm/5ppm
HCL	0-2000ppm/4%vol	T90≤50s	1 ppm	50ppm/100ppm
HCN	0-10ppm	T90≤50s	0.1ppm	3ppm/10ppm
CH ₄ (IR)	0-30ppm/200ppm	T90≤50s	0.1 ppm	5ppm/10ppm
VOCs	0-200ppm	T90≤200s	0.1ppm	10 ppm /20 ppm
CO ₂ (IR)	0-5.00%vol	T90≤60s	0.01%vol	1.00%vol/2.00%vol
C ₃ H ₈ (IR)	0-1999ppm	T90≤20s	0.1ppm	1000ppm/1500ppm
CO	0-5.00%vol (0-1%vol)	T90≤60s	0.01%vol (0.001%vol)	1.00%vol/2.00%vol (customize)
H ₂ S	0-5.00%vol	T90≤60s	0.01%Vol	1.00%vol/2.00%vol

product catalog



K60B

KELISAIKE



K60



K60-IV



K60-IV-P

Fixed/Wall-Mounted Gas Detector (Controller)



K800



K500



K700



K1000

Online Gas Analyzer ans CEMs



KF200




KF100



WT602



CEMs



AQMS

Breathing Safety Apparatus



EEBD



SABA



SCBA



FBCAR



PAPR

Other product





Radon

BW gas detector

MXCL

Gas sensor

Company Information



COMPANY APPEARANCE

THE OFFICE MEETING



WORKSHOP INSTRUMENT



- Nanjing Kelisaik Safety Equipment Co., Ltd. founded in 2004, Nanjing Kelisaik has three subsidiaries in Beijing, Xi'an and Xinjiang province, and over 30 domestic sales service centers.
- Standard products include the K60 series portable single gas detectors, K60-IV series multi gas detectors, K800 series fixed gas transmitters, K500 series wall-mounted gas detectors, K1000 series gas detector control panel units, KL99 series air breathing apparatuses, etc.
- Nanjing Kelisaik is also a factory with rich experience in OEM service, providing professional design and manufacturing of customized products.

Contact informations



Nanjing Kelisaik Safety Equipment Co., Ltd.



+86 25 8719 3262



manager@njklsk.cn



multi-gasdetection.com

Bldg 12, 2 Qingshuiting West Road, Nanjing, Jiangsu, China, 211102