



Basic Information

- Minimum Order Quantity: MOQ 1pc
- Price: USD 420
- Stock: 100pcs in stock
- Shipping Method: Express
- Description: Up to 5 sensors, built-in pump, color LCD, triple 90 dB alarm, rugged IP-rated case, CE certified
- Payment Terms: T/T



Product Specification

- Product Name: Portable Gas Detector For O2
- Detecting Gas: CO,H2S,O2,CO2,H2
- Power Supply: Built-in 3.7V Lithium Battery
- Alarm Type: Visual& Vibration Sound Alarm
- Color: Black
- Sampling Method: Diffusion Sampling Standard / Sampling Pump Optional
- Display: LCD
- Usage: Industrial Production
- Measure Range: 0-1000ppm,customize
- Response Time: T90<30s
- Warranty: One Year
- Battery: Lithium Rechargeable Battery
- Protection Grade: IP65
- Gas Sensor: Electrochemical Sensors



More Images



Product Description

K60IV P portable multi gas detector with pump

Engineered for confined-space entry and process-safety tasks, the K60-IV-P packs the power of up to five interchangeable sensors (O₂, LEL, H₂S, CO, SO₂ or other user-specified gases) into a palm-sized, pump-assisted instrument. A bright color LCD, 90 dB triple-alarm, and robust datalogging keep crews informed and compliant even in the harshest environments, while tool-free service access minimizes downtime.

K60-V Portable Multi Gas Detector



UK sensors (brands CITY, Alphasense, Dynamant etc.), US (brand Honeywell), Japanese and German sensors, ensuring high stability & sensitivity

CE/ ATEX approved. Gas detectors are approved under the ATEX directive.



- **IP66 Ingress Protection:** compact and durable body design, wider application environments
- **Optional sampling pump:** built-in pump or compatible with handy pump unit for confined space gases detection
- **Data Logger Function:** alarm history record can be uploaded to PC
- **Applicable in harsh environments:** -4 °F to 122°F (-20°C – +50°C), 0 – 95% RH, non-condensing (anti-splash)

Ultra-strong battery: 3.7 V rechargeable lithium battery (equipped with a charger) for over 10 hours continuous operation.



- **High response speed:** Specially designed main board for industrial use; 10+ years professional engineering team for technical solutions
- **OBM/ ODM/ OEM service:** with 14 years experience, specializing in gas detectors.

Key Features

Ultra-compact & light (≤ 350 g)—comfortable for all-day, one-handed use.

2 + 2-digit color LCD—instantly shows gas name, real-time concentration, and alarm status.

Integrated sample pump with quick-fit probe; also compatible with external pumps.

Triple alarm—90 dB audible siren, high-visibility LED flash, and strong vibration for noisy sites.

Rugged, water-resistant housing—shock- and concussion-proof for industrial or mining duty.

Tool-free access to pump, sensors, filter, and Li-ion battery for rapid maintenance.

Rechargeable battery > 5 h continuous operation; USB charging and data download.

Comprehensive self-test—sensors, battery, circuit integrity, and alarms verified at start-up.

100 k-point datalogger stores measurements and events for traceable reporting.

Standard accessories—operator's manual, probe, calibration hose, USB cable, universal charger, conversion plug.

Certifications—CE for global compliance.

The K60-IV-P delivers dependable, customizable multi-gas protection in a single, easy-to-use package—ideal for technicians who refuse to compromise on safety or portability.

Technical Specifications

Item:	portable multi-gas detector
Model NO.:	K60
Sensors:	UK sensors (brand CITY, Alphasense, Dynamant etc.), US (brand Honeywell), Japan and Germany sensors, ensuring high stability & sensitivity
Sensor service life:	2 years
Operating voltage:	3.7V Rechargeable lithium battery, continuously work for 5+ hours
Data interface:	USB
Display:	Color screen 2+2 digits LCD display
Data Storage:	9600pcs data record stock. Can be uploaded to PC
Alarm buzzer:	90db
Alarm mode:	Acousto optic alarm
Alarm error:	$\leq \pm 3\%$
Ambient temperature:	- 20 °C ~ + 50 °C
Relative humidity:	15~95%RH(non condensation)
Material:	ABS, slip silicone
Detecting method:	Pump
Pumping tube:	150cm
Dimension(mm):	133(L)*70(W)*36 (H)mm
Explosion-proof grade:	ExdII CT3
Weight :	0.5kg(with charger and detection probe)
Package:	carton
Pcs/ctn:	1pc/ctn
Ctn size:	182x132x110mm
Payment terms:	T/T
Warranty:	1 year

Mark: other customized gas types are also available.

Gas Types	Detection range	Response Time	Resolution	Alarm Values
O ₂	0-25%vol/30%vol	T90≤20s	0.1%vol	18.0%vol/23.0%vol
LEL	0-100%LEL	T90≤30s	1%LEL	25.0%LEL/50.0%LEL
CO	0-1000 ppm/2000ppm	T90≤30s	1 ppm	50ppm/100ppm
H ₂ S	0-200 ppm	T90≤30s	0.1 ppm	10ppm/20ppm
SO ₂	0-200ppm	T90≤30s	0.1 ppm	2 ppm /10 ppm
Cl ₂	0-20 ppm	T90≤30s	0.1 ppm	1 ppm /10 ppm
NH ₃	0-100ppm/200ppm	T90≤50s	1 ppm	25 ppm /50 ppm
NO ₂	0-200ppm	T90≤25s	0.1 ppm	3 ppm /10 ppm
NO	0-1000 ppm	T90≤50s	1 ppm	25 ppm /50 ppm
O ₃	0-5ppm/20ppm	T90≤30s	0.1ppm	0.3ppm/5ppm
PH ₃	0-10ppm	T90≤60s	0.1ppm	0.3ppm/5ppm
H ₂	0-2000ppm/4%vol	T90≤50s	1 ppm	50ppm /100ppm
HF	0-10ppm	T90≤50s	0.1ppm	3ppm /10ppm
HCL	0-30ppm/200ppm	T90≤50s	0.1 ppm	5ppm /10ppm
HCN	0-200ppm	T90≤200s	0.1ppm	10 ppm /20 ppm
CH ₄ (IR)	0-5.00%vol	T90≤60s	0.01%vol	1.00%vol/2.00%vol
VOCs	0-1999ppm	T90≤20s	0.1ppm	1000ppm/1500ppm
CO ₂ (IR)	0-5.00%vol (0-1%vol)	T90≤60s	0.01%vol (0.001%vol)	1.00%vol/2.00%vol (customize)
C ₃ H ₈ (IR)	0-5.00%vol	T90≤60s	0.01%Vol	1.00%vol/2.00%vol
HCN	0-50ppm	T90≤200s	0.1ppm	10ppm/20ppm

Mark: Customized 2-gas detector, 3-gas detector and 4-gas detector is welcome.



Nanjing Kelisaike Safety Equipment Co., Ltd.



+86 25 8719 3262



manager@njklsk.cn



multi-gasdetection.com

Bldg 12, 2 Qingshuiting West Road, Nanjing, Jiangsu, China, 211102