

High-Pressure Self-Contained Air Respirator Fire Safety Equipment

Our Product Introduction

for more products please visit us on multi-gasdetection.com

Basic Information

- Minimum Order Quantity: 1PC
- Stock: 1PC



Product Specification

- Model NO.: KL99
- Standard: Q/Kj015-2002
- Hydrostatic Pressure(MPa): 45
- Working Pressure(MPa): 30
- Gas: Compressed Air
- Gas Cylinder Volume(L): 2L,3L,4.7L,6.8L,9L
- Max Low(L/Min): 300
- Inhalation Resistance(PA): <588
- Exhalation Resistance(PA): <687
- Equip: 6.8L Carbon Fiber Cylinder
- Service Time: More Than 60mins At 30L/Min
- Transport Package: Carton/Set
- Specification: 76.5*28.5*52
- Trademark: KELISAIKE
- Origin: Nanjing China



More Images



Product Description



>> Product Information

Type: KL99 composite cylinder Material: Carbon fiber composites
 Hydrostatic pressure(Mpa): 45 Working pressure(Mpa): 30
 Gas: Compressed air Gas cylinder volume(L): 2L,3L,4.7L,6.8L,9L
 Max flow(L/min): 300 Inhalation resistance(Pa): <588
 Exhalation resistance(Pa): <687 Alarm pressure(Mpa): 4~6
 Alarm(dB): ≥90

No.	Volume (L)	Outside Diameter(mm)	Wall Thickness(mm)	Working pressure(Mpa)	Weight(kg)	Length(mm)
KL99-C1	2	96	M18*1.5	30	1.5	433
KL99-C2	3	114	M18*1.5	30	2.1	446
KL99-C3	4.7	137	M18*1.5	30	3	492
KL99-C4	6.8	157	M18*1.5	30	3.9	530
KL99-C5	9	175	M18*1.5	30	5.3	560

KL99-SCBA



CE/ MED approved, meeting
 EN137, EN136 standards.

Air Cylinders: More robust and safer four-layer composite structure design; aluminum alloy inner bladder; carbon fiber; glass fiber; epoxy resin

Design of a CFRP cylinder:



Reduced Pressure Assembly: Stable output pressure of the compressor. Despite featuring a small volume carbon fiber tank, the high pressure air in the tank can be quickly converted to standard low pressure breathable air.

Full Mask: Plug-in structure for quick connection with the demand valve; Leak tight mask, made of high quality flame resistant silicon rubber; Top silicon rubber oronasal cover, soft and high temperature resistant; Flame resistant reticulated hood and strap, easy to wear; High-intensity sound transmission diaphragm.



- **Back Plate Assembly** Consisting of a back plate, shoulder straps, a waist belt, a buckle, a pressure reducer holder and a cylinder fastener. Designed according to ergonomics, complying with the back shape of 5. human body.
- **Injection moulded**, with flame resistant engineering plastics and carbon fiber. The shoulder straps and belt are made of Nomex or KEVLAR, tear-resistant and flame-retardant.



THE FACTORY

Nanjing KELISAIKE has passed ISO9001 International Quality System Certification, which ensures all products' excellent performance and competitive prices.



PACKAGING & DELIVERY

Delivery Time

7-10 days after payment



packing interior:
good quality plastic case



Dim:76*28*52mm
G.W:27KG



COMPANY APPEARANCE

THE OFFICE MEETING



WORKSHOP INSTRUMENT



- Nanjing Kelisaik Safety Equipment Co., Ltd. founded in 2004, Nanjing Kelisaik has three subsidiaries in Beijing, Xi'an and Xinjiang province, and over 30 domestic sales service centers.
- Standard products include the K60 series portable single gas detectors, K60-IV series multi gas detectors, K800 series fixed gas transmitters, K500 series wall-mounted gas detectors, K1000 series gas detector control panel units, KL99 series air breathing apparatuses, etc.
- Nanjing Kelisaik is also a factory with rich experience in OEM service, providing professional design and manufacturing of customized products.

>> Our Exhibition



>> Our Certificates



We have obtained CE, ISO and other international certificates for different market requirements.

>> Product Application Show



- The company's products are widely used in fields of petroleum, chemical, gas transmission and distribution, warehousing, municipal gas supply, fire fighting, environmental protection, metallurgy, pharmacy, energy and power industry.



Nanjing Kelisaik Safety Equipment Co., Ltd.



+86 25 8719 3262



manager@njklsc.cn



multi-gasdetection.com

Bldg 12, 2 Qingshuiting West Road, Nanjing, Jiangsu, China, 211102